

Module SLE G7 FASHION EXC

Modules SLE excite



LES13 + LES15 with housing



LES17 with housing



LES21 with housing

Product description

- _ Optimized light spectrum for perfect fashion presentation
- _ For operating with SELV Driver
- _ Warm, thrilling colours with a high saturation combined with a pure and shiny white
- _ Excellent thermal management by COB technology
- _ Uniform radiation with Dam&Fill technology
- _ Integrated LED module
- _ Cooling required
- _ Flexible operating mode
- _ HE ... High Efficiency, NM ... Nominal Mode, HO ... High Output
- _ Long lifetime: 55,000 hours
- _ 5 years guarantee (conditions at <https://www.tridonic.com/manufacture-guarantee-conditions>)

Optical properties

- _ Useful luminous flux 5,421 lm at Irated and tp = 25 °C
- _ Best balanced Fashion light for all colours (typical CRI 95)
- _ Small colour tolerance (MacAdam 3)

Mechanical properties

- _ Module dimension LES13, LES15, LES17 and LES21
- _ Housing with Snap-On feature for easy reflector mounting
- _ 50 mm housing with 35 mm mounting hole distance acc. to Zhaga
- _ Fixing holes for M3 screws

Website

<http://www.tridonic.com/28002701>



Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street




Decorative




High bay

Module SLE G7 FASHION EXC


Modules SLE excite




Dimensions in mm, *optical LES




Dimensions in mm, *optical LES



Dimensions in mm, *optical LES



Dimensions in mm, *optical LES



Dimensions in mm, *optical LES

Ordering data

| Type | Article number | Colour temperature | Packaging, carton | Weight per pc. |
|--------------------------------------|----------------|--------------------|-------------------|----------------|
| SLE G7 13mm – Without housing | | | | |
| SLE G7 13mm 3000lm FASHION R EXC | 28002701 | 3,250 K | 20 pc(s). | 0.001 kg |
| SLE G7 15mm – Without housing | | | | |
| SLE G7 15mm 4000lm FASHION R EXC | 28002706 | 3,250 K | 20 pc(s). | 0.002 kg |
| SLE G7 15mm – With housing | | | | |
| SLE G7 15mm 4000lm FASHION H EXC | 28002745 | 3,250 K | 50 pc(s). | 0.007 kg |
| SLE G7 17mm – With housing | | | | |
| SLE G7 17mm 5000lm FASHION H EXC | 28002746 | 3,250 K | 50 pc(s). | 0.007 kg |
| SLE G7 21mm – With housing | | | | |
| SLE G7 21mm 6000lm FASHION H EXC | 28002758 | 3,250 K | 50 pc(s). | 0.007 kg |

Technical data

| | |
|---|----------------------|
| Beam characteristic | 115° |
| Ambient temperature t_a | -30 ... +80 °C |
| t_p rated | 65 °C |
| t_c ^① | 105 °C |
| I _{rated} for LES13 | 500 mA |
| I _{rated} for LES15 | 900 mA |
| I _{rated} for LES17 | 1,050 mA |
| I _{rated} for LES21 | 1,400 mA |
| I _{max} for LES13 ^① | 990 mA |
| I _{max} for LES15 ^① | 1,320 mA |
| I _{max} for LES17 ^① | 1,540 mA |
| I _{max} for LES21 ^① | 2,200 mA |
| Max. permissible LF current ripple for LES13 | 1,440 mA |
| Max. permissible LF current ripple for LES15 | 1,920 mA |
| Max. permissible LF current ripple for LES17 | 1,680 mA |
| Max. permissible LF current ripple for LES21 | 2,400 mA |
| Max. permissible peak current for LES13 | 1,800 mA / max. 8 ms |
| Max. permissible peak current for LES15 | 2,160 mA / max. 8 ms |
| Max. permissible peak current for LES17 | 2,520 mA / max. 8 ms |
| Max. permissible peak current for LES21 | 3,600 mA / max. 8 ms |
| Max. working voltage for insulation SELV ^② | < 60 V |
| Insulation test voltage | 0.5 kV |
| CTI of the printed circuit board | ≥ 600 |
| Colour tolerance | 3 SDCM |
| ESD classification | Severity level 4 |
| Risk group (IEC 62471) | RG1 |
| Type of protection | IP00 |
| Lumen maintenance L70B50 | 55,000 h |
| Guarantee (conditions at www.tridonic.com) | 5 Year(s) |

Approval marks**Standards**

EN 62031, EN 62471, IEC 62717, IEC 61000-4-2, UL 8750

Specific technical data

| Type | Article number | Photometric code | Useful luminous flux at $t_p = 25\text{ °C}$ ^③ | Expected luminous flux at t_p rated ^④ | Typ. forward current | Min. forward voltage at t_p rated | Max. forward voltage at $t_p = 25\text{ °C}$ | Power consumption P_{on} at $t_p = 25\text{ °C}$ ^⑤ | Efficacy of the module at $t_p = 25\text{ °C}$ | Expected efficacy of the module at t_p rated | Colour rendering index CRI |
|--|----------------|------------------|---|--|----------------------|-------------------------------------|--|---|--|--|----------------------------|
| SLE 13mm 3000lm – Operating mode HE at 350 mA | | | | | | | | | | | |
| SLE G7 13mm 3000lm FASHION R EXC | 28002701 | 932/359 | – | 1,530 lm | 350 mA | 33.6 V | 34.1 V | – | – | 129 lm/W | >90 |
| SLE 13mm 3000lm – Operating mode NM at 500 mA | | | | | | | | | | | |
| SLE G7 13mm 3000lm FASHION R EXC | 28002701 | 932/359 | 2,290 lm | 2,140 lm | 500 mA | 34.6 V | 35.1 V | 17.6 W | 130 lm/W | 123 lm/W | >90 |
| SLE 13mm 3000lm – Operating mode HO at 900 mA | | | | | | | | | | | |
| SLE G7 13mm 3000lm FASHION R EXC | 28002701 | 932/359 | – | 3,630 lm | 900 mA | 37.0 V | 37.5 V | – | – | 108 lm/W | >90 |
| SLE 15mm 4000lm – Operating mode HE at 500 mA | | | | | | | | | | | |
| SLE G7 15mm 4000lm FASHION R EXC | 28002706 | 932/359 | – | 2,180 lm | 500 mA | 33.4 V | 33.9 V | – | – | 130 lm/W | >90 |
| SLE G7 15mm 4000lm FASHION H EXC | 28002745 | 932/359 | – | 2,046 lm | 500 mA | 33.4 V | 33.9 V | – | – | 122 lm/W | >90 |
| SLE 15mm 4000lm – Operating mode NM at 900 mA | | | | | | | | | | | |
| SLE G7 15mm 4000lm FASHION R EXC | 28002706 | 932/359 | 4,020 lm | 3,760 lm | 900 mA | 35.0 V | 35.5 V | 32.0 W | 126 lm/W | 119 lm/W | >90 |
| SLE G7 15mm 4000lm FASHION H EXC | 28002745 | 932/359 | 3,773 lm | 3,529 lm | 900 mA | 35.0 V | 35.5 V | 32.0 W | 118 lm/W | 111 lm/W | >90 |
| SLE 15mm 4000lm – Operating mode HO at 1,200 mA | | | | | | | | | | | |
| SLE G7 15mm 4000lm FASHION R EXC | 28002706 | 932/359 | – | 4,880 lm | 1,200 mA | 36.1 V | 36.6 V | – | – | 113 lm/W | >90 |
| SLE G7 15mm 4000lm FASHION H EXC | 28002745 | 932/359 | – | 4,580 lm | 1,200 mA | 36.1 V | 36.6 V | – | – | 106 lm/W | >90 |
| SLE 17mm 5000lm – Operating mode HE at 500 mA | | | | | | | | | | | |
| SLE G7 17mm 5000lm FASHION H EXC | 28002746 | 932/359 | – | 1,876 lm | 500 mA | 33.3 V | 34.0 V | – | – | 113 lm/W | >90 |
| SLE 17mm 5000lm – Operating mode NM at 1,050 mA | | | | | | | | | | | |
| SLE G7 17mm 5000lm FASHION H EXC | 28002746 | 932/359 | 4,000 lm | 3,743 lm | 1,050 mA | 34.8 V | 35.5 V | 37.3 W | 107 lm/W | 103 lm/W | >90 |
| SLE 17mm 5000lm – Operating mode HO at 1,400 mA | | | | | | | | | | | |
| SLE G7 17mm 5000lm FASHION H EXC | 28002746 | 932/359 | – | 4,847 lm | 1,400 mA | 35.6 V | 36.3 V | – | – | 97 lm/W | >90 |
| SLE 21mm 6000lm – Operating mode HE at 700 mA | | | | | | | | | | | |
| SLE G7 21mm 6000lm FASHION H EXC | 28002758 | 932/359 | – | 2,656 lm | 700 mA | 33.3 V | 34.0 V | – | – | 114 lm/W | >90 |
| SLE 21mm 6000lm – Operating mode NM at 1,400 mA | | | | | | | | | | | |
| SLE G7 21mm 6000lm FASHION H EXC | 28002758 | 932/359 | 5,421 lm | 5,068 lm | 1,400 mA | 34.7 V | 35.4 V | 49.6 W | 109 lm/W | 104 lm/W | >90 |
| SLE 21mm 6000lm – Operating mode HO at 2,000 mA | | | | | | | | | | | |
| SLE G7 21mm 6000lm FASHION H EXC | 28002758 | 932/359 | – | 6,984 lm | 2,000 mA | 35.7 V | 36.4 V | – | – | 98 lm/W | >90 |

① See derating curves in data sheet section 2.3.

② The detailed explanation, see data sheet section 3.1.

③ Tolerance of useful light flux - 0 % / + 15 %. Measurement uncertainty $\pm 10\%$.④ Tolerance of expected light flux - 0 % / + 15 %. Measurement uncertainty $\pm 10\%$. Based on calculation.⑤ Tolerance of power consumption P_{on} $\pm 10\%$. Measurement uncertainty $\pm 5\%$.

Housing for SLE


Accessory



LES13

- Product description**
- _ Housing for SLE
 - _ Diameter: 35 mm
 - _ Material: Lexan Resin 943
 - _ M3 screws with flat head, max. head diameter of 6 mm and max. torque for fixing is 0.5 Nm

Website
<http://www.tridonic.com/28003026>



SLE G7 HOUSING LES13/15

| Ordering data | | | |
|--------------------------|----------------|----------------|----------------|
| Type | Article number | Packaging, bag | Weight per pc. |
| SLE G7 HOUSING LES 13/15 | 28003026 | 500 pc(s). | 0.002 kg |

1. Standards

EN 62031
 EN 62471
 IEC 62717
 IEC 61000-4-2
 UL 8750 (for CLASS2 circuits and dry locations)

1.1 Glow wire test for housing variants

according to IEC 60695-2-11 with increased temperature of 850 °C passed.

1.2 Photometric code

Key for photometric code, e. g. 830 / 359

| 1 st digit | 2 nd + 3 rd digit | 4 th digit | 5 th digit | 6 th digit |
|-----------------------|---|------------------------------------|---|---|
| Code | CRI | Colour temperature in Kelvin x 100 | MacAdam after 25% of the lifetime (max.6000h) | Luminous flux after 25% of the lifetime (max.6000h) |
| 7 | 70 – 79 | MacAdam initial | (max.6000h) | Code |
| 8 | 80 – 89 | | | Luminous flux |
| 9 | ≥90 | | | |
| | | | | 7 ≥ 70 % |
| | | | | 8 ≥ 80 % |
| | | | | 9 ≥ 90 % |

1.3 Energy classification

| Type | Colour temperature | Forward current | Energy classification | Energy consumption |
|--------------------------------------|--------------------|-----------------|-----------------------|--------------------|
| SLE G7 13mm – Without housing | | | | |
| SLE G7 13mm 3000lm FASHION R EXC | 3,250 K | 500 mA | E | 18 kWh / 1,000 h |
| SLE G7 15mm – Without housing | | | | |
| SLE G7 15mm 4000lm FASHION R EXC | 3,250 K | 900 mA | E | 32 kWh / 1,000 h |
| SLE G7 15mm – With housing | | | | |
| SLE G7 15mm 4000lm FASHION H EXC | 3,250 K | 900 mA | E | 32 kWh / 1,000 h |
| SLE G7 17mm – With housing | | | | |
| SLE G7 17mm 5000lm FASHION H EXC | 3,250 K | 1,050 mA | E | 38 kWh / 1,000 h |
| SLE G7 21mm – With housing | | | | |
| SLE G7 21mm 6000lm FASHION H EXC | 3,250 K | 1,400 mA | E | 50 kWh / 1,000 h |

Energy label and further information at www.tridonic.com in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

2. Thermal details

2.1 tp point, ambient temperature and lifetime


The temperature at tp reference point is crucial for the light output and lifetime of a LED product.

For SLE G7 a tp temperature of 65 °C has to be complied in order to achieve an optimum between heat sink requirements, light output and lifetime.

Compliance with the maximum permissible reference temperature at the tp point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

To check the tc / tp temperature, the temperature sensor has to be mounted on the PCB at the marked position as stated in the drawing.



2.2 Storage and humidity


| | |
|---------------------|----------------|
| storage temperature | -30 ... +80 °C |
|---------------------|----------------|

Operation only in non condensing environment.


Humidity during processing of the module should be between 0 to 85 %.

2.3 Derating curves


SLE G7 13mm 3000lm FASHION EXC




SLE G7 15mm 4000lm FASHION EXC



SLE G7 17mm 5000lm FASHION EXC



SLE G7 21mm 6000lm FASHION EXC**2.4 Thermal design and heat sink**

The rated life of LED products depends to a large extent on the temperature. If the permissible temperature limits are exceeded, the life of the SLE G7 will be greatly reduced or the SLE G7 may be destroyed.

2.5 Heat sink values**SLE G7 13mm 3000lm 9x0 EXC**

| ta | tp | Operating current | R _{th, hs-a} |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 350 mA | 3.4 K/W |
| 35 °C | 65 °C | 350 mA | 2.6 K/W |
| 45 °C | 65 °C | 350 mA | 1.7 K/W |
| 25 °C | 65 °C | 500 mA | 2.3 K/W |
| 35 °C | 65 °C | 500 mA | 1.7 K/W |
| 45 °C | 65 °C | 500 mA | 1.2 K/W |
| 25 °C | 65 °C | 900 mA | 1.2 K/W |
| 35 °C | 65 °C | 900 mA | 0.9 K/W |
| 45 °C | 65 °C | 900 mA | 0.6 K/W |

SLE G7 15mm 4000lm 9x0 EXC

| ta | tp | Operating current | R _{th, hs-a} |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 500 mA | 2.4 K/W |
| 35 °C | 65 °C | 500 mA | 1.8 K/W |
| 45 °C | 65 °C | 500 mA | 1.2 K/W |
| 25 °C | 65 °C | 900 mA | 1.3 K/W |
| 35 °C | 65 °C | 900 mA | 1.0 K/W |
| 45 °C | 65 °C | 900 mA | 0.6 K/W |
| 25 °C | 65 °C | 1,200 mA | 0.9 K/W |
| 35 °C | 65 °C | 1,200 mA | 0.7 K/W |
| 45 °C | 65 °C | 1,200 mA | 0.5 K/W |

SLE G7 17mm 5000lm 9x0 EXC

| ta | tp | Operating current | R _{th, hs-a} |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 500 mA | 2.3 K/W |
| 35 °C | 65 °C | 500 mA | 1.7 K/W |
| 45 °C | 65 °C | 500 mA | 1.1 K/W |
| 25 °C | 65 °C | 1,050 mA | 1.0 K/W |
| 35 °C | 65 °C | 1,050 mA | 0.7 K/W |
| 45 °C | 65 °C | 1,050 mA | 0.4 K/W |
| 25 °C | 65 °C | 1,400 mA | 0.7 K/W |
| 35 °C | 65 °C | 1,400 mA | 0.5 K/W |
| 45 °C | 65 °C | 1,400 mA | 0.3 K/W |

SLE G7 21m 6000lm 9x0 EXC

| ta | tp | Operating current | R _{th, hs-a} |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 700 mA | 1.6 K/W |
| 35 °C | 65 °C | 700 mA | 1.2 K/W |
| 45 °C | 65 °C | 700 mA | 0.8 K/W |
| 25 °C | 65 °C | 1,400 mA | 0.7 K/W |
| 35 °C | 65 °C | 1,400 mA | 0.5 K/W |
| 45 °C | 65 °C | 1,400 mA | 0.3 K/W |
| 25 °C | 65 °C | 2,000 mA | 0.5 K/W |
| 35 °C | 65 °C | 2,000 mA | 0.3 K/W |
| 45 °C | 65 °C | 2,000 mA | 0.2 K/W |

Notes

The actual cooling can differ because of the material, the structural shape, outside influences and the installation situation. A thermal connection between SLE G7 and heat sink with heat-conducting paste or heat conducting adhesive film is absolutely necessary.

Additionally the SLE G7 has to be fixed on the heat sink with M3 screws to optimise the thermal connection.

Use of thermal interface material with thermal conductivity of $\lambda > 1 \text{ W/mK}$ and layer thickness of interface material with max. 50 μm or a similar interface material where the quotient of layer thickness and thermal conductivity $b < 50 \text{ mmK/W}$.

3. Installation / wiring

3.1 Electrical supply/choice of LED driver

SLE G7 from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED driver which complies with the relevant standards. The use of LED drivers from Tridonic in combination with SLE G7 guarantees the necessary protection for safe and reliable operation.

If a LED driver other than Tridonic is used, it must provide the following protection:

- Short-circuit protection
- Overload protection
- Overtemperature protection



SLE G7 must be supplied by a constant current LED driver. Operation with a constant voltage LED driver will lead to an irreversible damage of the module. Wrong polarity can damage the SLE G7.



SLE G7 must not be operated with nonSELV LED driver.




SLE G7 are basic insulated up to 60 V SELV against ground and can be mounted directly on earthed metal parts of the luminaire. If the max. output voltage of the LED driver (also against earth) is above 60 V SELV, an additional insulation between LED module and heat sink is required (for example by insulated thermal pads) or by a suitable luminaire construction.


At voltages > 60 V an additional protection against direct touch (test finger) to the light emitting side of the module has to be guaranteed. This is typically achieved by means of a non removable light distributor over the module.

3.2 Wiring

Wiring with housing (LES15)




Wiring with housing (LES17 and LES21)




Wiring without housing


LES13




LES15



LES17 + LES21



Wiring example**3.5 EOS/ESD safety guidelines**

The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice.

For further information for EOS/ESD safety guidelines and the ESD classification please refer to the brochure entitled <http://www.tridonic.com/esd-protection>.


3.3 Wiring type and cross section for housing variants

For wiring use solid wire from 0.5 to 0.75 mm² or stranded wire with soldered ends of 0.5 mm².

For the push-wire connection you have to strip the insulation (6 – 7 mm).

Loosen wire through twisting and pulling.

wire preparation:

**3.4 Mounting instruction**

SLE G7 from Tridonic which have to be installed on a heat sink have to be connected with heat-conducting paste or heat conducting adhesive film and fixed with M3 screws.

The fixing/cooling surface must be cleaned by removing all dirt, dust and grease before installing the LED modules.

None of the components of the SLE G7 (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.



Max. torque for fixing: 0.3 Nm (LES13, LES15)
0.5 Nm (LES17, LES21)

The LED modules are mounted with 2 screws per module. In order not to damage the modules only rounded head screws and an additional plastic flat washer (notice working temperature) or rounded head screw with collar (ISO 7380-2) with head diameter ≥ 6.9 mm must be used for LED modules without housing (for LES13, LES15).

For further information please refer to the brochure entitled "Technical Design-In-Guide SLE GEN7".



Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.

Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.

Avoid corrosive atmosphere during usage and storage.

4. Lifetime

4.1 Lifetime, lumen maintenance and failure rate

The light output of an LED module decreases over the lifetime, this is characterized with the L value. L70 means that the LED module will give 70 % of its initial luminous flux. This value is always related to the number of operation hours and therefore defines the lifetime of an LED module.

As the L value is a statistical value and the lumen maintenance may vary over the delivered LED modules. The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value.

In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

4.2 Lumen maintenance

Lifetime declarations are informative and represent no warranty claim. Preliminary calculated lifetime data until LM80 test reports are available

SLE G7 13mm 3000lm EXC

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 350 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 500 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 900 mA | 65 °C | 37,000 h | 51,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 37,000 h | 51,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 13,000 h | 20,000 h | 31,000 h | 49,000 h | 50,000 h | >55,000 h |

SLE G7 15mm 4000lm EXC

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 500 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 900 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,200 mA | 65 °C | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 13,000 h | 20,000 h | 31,000 h | 49,000 h | 51,000 h | >55,000 h |

SLE G7 17mm 5000lm EXC

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 500 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,050 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,400 mA | 65 °C | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 13,000 h | 20,000 h | 31,000 h | 50,000 h | 51,000 h | >55,000 h |

SLE G7 21mm 6000lm EXC

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 700 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 40,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,400 mA | 65 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | 50,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 26,000 h | 37,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 2,000 mA | 65 °C | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 85 °C | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| | 105 °C | 13,000 h | 20,000 h | 31,000 h | 50,000 h | 51,000 h | >55,000 h |

5. Electrical values

5.1 Declaration of electrical parameters

I_{rated} ... Nominal operating current the module is designed for.


I_{max} ... Max. permissible continuous operating current incl. The tolerances of the LED driver.

Max. permissible LF current ripple ... Max. output current of the LED driver incl. Tolerances and LF current ripple must not exceed this value.


Max. permissible peak current ... The max. output peak current of the LED driver must not exceed this value.

5.2 Typ. forward voltage vs. forward current


SLE G7 13mm 3000lm xxx EXC




SLE G7 17mm 5000lm xxx EXC




SLE G7 15mm 4000lm xxx EXC



SLE G7 21mm 6000lm xxx EXC



5.3 Forward voltage vs. T_p temperature



The diagrams based on statistic values.
The real values can be different.

6. Photometric characteristics


6.1 Coordinates and tolerances according to CIE 1931 and colour rendering

The specified colour coordinates are measured integral after a settling time of 100 ms. The current impuls depends on the module type. The ambient temperature of the measurement is $t_a = 25^\circ\text{C}$. The measurement tolerance of the colour coordinates are ± 0.01 .

| Module type | Current impulse |
|--------------------------------|-----------------|
| SLE G7 13mm 3000lm FASHION EXC | 500 mA |
| SLE G7 15mm 4000lm FASHION EXC | 900 mA |
| SLE G7 17mm 5000lm FASHION EXC | 1,050 mA |
| SLE G7 21mm 6000lm FASHION EXC | 1,400 mA |


3,250 K – CRI90

| | x0 | y0 |
|--------|--------|--------|
| Centre | 0.4177 | 0.3918 |




MacAdam ellipse: 3SDCM


| TM30 | | CRI | |
|------|-----|-----|----|
| Rf | Rg | Ra | R9 |
| 89 | 106 | 94 | 93 |



Colour vector graphic




— Reference source
— Test source




6.2 Light distribution

The optical design of the SLE product line ensures optimum homogeneity for the light distribution.




6.3 Relative luminous flux vs. tp temperature






6.4 Relative luminous flux vs. operating current

SLE G7 13mm 3000lm xxx EXC



SLE G7 15mm 4000lm xxx EXC



SLE G7 17mm 5000lm xxx EXC**SLE G7 21mm 6000lm xxx EXC****7. Miscellaneous****7.1 Additional information**

Additional technical information at www.tridonic.com → Technical Data

Guarantee conditions at www.tridonic.com → Services

Lifetime declarations are informative and represent no warranty claim.

Colour rendering information are typical values and represent no warranty claim.