

OVE Austrian Electrotechnical Association
Eschenbachgasse 9 | 1010 Wien | Austria
ZVR: 327279890 | www.ove.at



OVE Certification
Kahlenberger Str. 2A | 1190 Wien | Austria
T +43 1 370 58 06 | certification@ove.at

ENEC Certification Body registered under ID # 11.

Validity of ENEC Licences can be checked at www.enec.com

LICENCE

to use the European Mark



Licence No.: **7590-316**

Date of issue: Wien, 2022 06 09
Rev. No.: 01 Wien, 2022 09 23

OVE the Austrian Electrotechnical Association as signatory to the **"Agreement on the use of a commonly agreed Mark of Conformity for certain electrical equipment complying with European Standards"** hereby grants the right to label the products mentioned hereunder and listed in the Annex with the Mark(s) shown above to the following company

Licenceholder: **Tridonic GmbH & Co KG**
Färbergasse 15
6851 Dornbirn
Austria

Product: **Electronic control gears for LED-modules**

Trade Mark: **TRIDONIC**

Series/Type: **LC ... flexC NF SC EXC3**

Basis for this given right is the conformity of the products with the requirements of the relevant Standard(s) as listed in the Annex and the fulfilment of articles 8 and 9 of the ENEC-Agreement by the manufacturer. This licence refers to the tested specimen and to all products manufactured strictly identical to the submitted one.

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

Österreichischer Verband für Elektrotechnik
Head of OVE Certification

T. Neumayer

Digitally signed by T. Neumayer
Email=t.neumayer@ove.at

Dipl.-Ing. T. Neumayer



OVE Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.



<i>Hersteller Manufacturer</i>	Tridonic GmbH & Co KG Färbergasse 15 6851 Dornbirn Austria
<i>Fertigungsstätte(n) Factory location(s)</i>	ID: 40926
<i>Typenbezeichnung Type reference</i>	LC ... flexC NF SC EXC3, see page 4
<i>* Prüfbericht Test Report</i>	TR 87837-0013-01 ECS, TR 87837-0013-02 ECS, TR 87837-0014-01 ECS, TR 87837-0014-02 ECS, TR 87837-0013-01a ECS, TR 87837-0013-02a ECS
<i>Nationale Bestimmung(en) National Standard(s)</i>	OVE EN 61347-1:2021-09-01 OVE EN 61347-2-13:2017-11-01 OVE EN IEC 62384:2021-04-01
<i>Europannorm(en) European Standard(s)</i>	EN 61347-1:2015 + A1:2021 EN 61347-2-13:2014 + A1:2017 EN IEC 62384:2020
<i>* Ersatz für Zertifikat Superseded licence</i>	7590-316 dated 2022 06 09 Items modified are marked with an asterisk (*)
<i>Anmerkung(en) Remark(s)</i>	Complies with the additional requirements for emergency lighting according Annex J of EN 61347-2- 13:2014+A1:2017. CTF Stage 3

OVE Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

<i>Nennspannung</i> <i>Rated voltage</i>	AC 220-240 V, 50/60 Hz; DC 220-240 V
<i>Nennstrom (sec.)</i> <i>Rated current (sec.)</i>	see page 4
<i>Höchste Ausgangsspannung</i> <i>Max. output voltage</i>	see page 4
<i>Nennleistung</i> <i>Rated power</i>	see page 4
<i>Schutzklasse</i> <i>Class of protection</i>	CI.II (when used as independent controlgear with optional Clip-on strain relief set)
<i>Max. Betriebstemperatur tc</i> <i>Rated max. operating temperature tc</i>	see page 4
<i>Umgebungstemperatur ta</i> <i>Rated ambient temperature ta</i>	see page 4
<i>Maximale Gehäusetemperatur</i> <i>Rated maximum case temperature</i>	110°C
<i>Kurzschlußschutz</i> <i>Short-circuit protection</i>	Inherently short circuit proof controlgear.
<i>Klassifikation</i> <i>Classification</i>	Built-in control gear with clip-on strain relief parts as independent controlgear, constant current type.

OVE Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

TRADEMARK / TYPECODE			Classification B...Built-in	Rated output current	Maximum output voltage SELV (no-load)	Rated output power	Rated max. operating temperature (tc) ²	Maximum ambient temperature (ta) ²	Maximum case temperature	Circuit power factor (230V, 50Hz, full load)	Case
TRIDONIC											Metal (M) Plastic (P)
				[mA]	[V]	[W]	[°C]	[°C]	[°C]	λ	
1	LC 14/100-400/42 flexC NF SC EXC3		B ¹	100-400	60	14	70/75	50	110	0,32C-0,9C	P
*	2 LC 28/300-700/42 flexC NF SC EXC3		B ¹	300-700	60	28	80	45*/50	110	0,4C-0,93C	P
3	LC 38/650-1050/42 flexC NF SC EXC3		B ¹	650-1050	60	38	87	45*/50	110	0,5C-0,95	P

¹ Independent control gear using clip-on strain-relief parts.

² Depending on selected output current, see respective datasheet.

* For built-in use ta = 50°C

OVE Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.