

OVE Austrian Electrotechnical Association
Eschenbachgasse 9 | 1010 Wien | Austria
ZVR: 327279890 | www.ove.at



OVE Certification
Kahlenberger Str. 2A | 1190 Wien | Austria
T +43 1 370 58 06 | certification@ove.at

ENEC Certification Body registered under ID # 11.

Validity of ENEC Licences can be checked at www.enec.com

LICENCE

to use the European Mark



Licence No.: **7590-269**

Date of issue: Wien, 2020 07 10
Rev. No.: 01 Wien, 2024 04 15

OVE the Austrian Electrotechnical Association as signatory to the **"Agreement on the use of a commonly agreed Mark of Conformity for certain electrical equipment complying with European Standards"** hereby grants the right to label the products mentioned hereunder and listed in the Annex with the Mark(s) shown above to the following company

Licensee: **Tridonic GmbH & Co KG**
Färbergasse 15
6851 Dornbirn
Austria

Product: **Electronic control gears for LED-modules**

Trade Mark: **TRIDONIC**

Series/Type: **LC ... flexCC Ip SNC3**

Basis for this given right is the conformity of the products with the requirements of the relevant Standard(s) as listed in the Annex and the fulfilment of articles 8 and 9 of the ENEC-Agreement by the manufacturer. This licence refers to the tested specimen and to all products manufactured strictly identical to the submitted one.

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

Österreichischer Verband für Elektrotechnik
Head of OVE Certification

T. Neumayer

Digitally signed by T. Neumayer
Email=t.neumayer@ove.at

Dipl.-Ing. T. Neumayer



OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.



| | |
|--|--|
| <i>Hersteller Manufacturer</i> | Tridonic GmbH & Co KG Färbergasse 15 6851 Dornbirn Austria |
| <i>Fertigungsstätte(n) Factory location(s)</i> | ID: 89012 |
| <i>Typenbezeichnung Type reference</i> | LC 25/200-350/70 flexCC Ip SNC3, LC 35/200-350/121 flexCC Ip SNC3, LC 50/200-350/170 flexCC Ip SNC3, LC 65/200-350/210 flexCC Ip SNC3, see page 4 |
| * <i>Prüfbericht Test Report</i> | TGM-VA EE 38374 ECS-1/ECS-2, TGM-VA EE 38375 ECS-1/ECS-2, TGM-VA EE 38376 ECS-1/ECS-2, TR 7590-0070-02 |
| * <i>Nationale Bestimmung(en) National Standard(s)</i> | OVE EN 61347-1:2021-09-01 OVE EN 61347-2-13:2017-11-01 OVE EN IEC 62384:2021-04-01 |
| * <i>Europannorm(en) European Standard(s)</i> | EN 61347-1:2015 + A1:2021 EN 61347-2-13:2014 + A1:2017 EN IEC 62384:2020 |
| * <i>Ersatz für Zertifikat Superseded licence</i> | 7590-269 dated 2020 07 10 Items modified are marked with an asterisk (*) |
| * <i>Anmerkung(en) Remark(s)</i> | -- |

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

| | |
|---|---|
| <i>Nennspannung</i> <i>Rated voltage</i> | AC 220-240 V, 50/60 Hz |
| <i>Nennstrom (sec.)</i> <i>Rated current (sec.)</i> | see page 4 |
| <i>Höchste Ausgangsspannung</i> <i>Max. output voltage</i> | see page 4 |
| <i>Nennleistung</i> <i>Rated power</i> | see page 4 |
| <i>Max. Betriebstemperatur tc</i> <i>Rated max. operating temperature tc</i> | see page 4 |
| <i>Umgebungstemperatur ta</i> <i>Rated ambient temperature ta</i> | see page 4 |
| <i>Maximale Gehäusetemperatur</i> <i>Rated maximum case temperature</i> | 110°C |
| <i>Kurzschlußschutz</i> <i>Short-circuit protection</i> | Short circuit proof control gear. |
| <i>Klassifikation</i> <i>Classification</i> | Built-in electronic controlgears, constant current type. |

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

| TRADEMARK / TYPECODE | | | Rated output current | Maximum output voltage (no-load) | Rated output power | Rated max. operating temperature (tc) | Maximum ambient temperature (ta) | Maximum case temperature | Circuit power factor (230V, 50Hz, full load) ¹ | Case |
|----------------------|---|----------------------------------|----------------------|----------------------------------|--------------------|---------------------------------------|----------------------------------|--------------------------|---|------------|
| TRIDONIC | | | | | | | | | | Metall (M) |
| | | | [mA] | [V] | [W] | [°C] | [°C] | [°C] | λ | |
| * | 1 | LC 25/200-350/70 flexCC Ip SNC3 | 200-350 | 270 | 25 | 75 | 60 | 110 | 0,46C – 0,90C | M |
| * | 2 | LC 35/200-350/121 flexCC Ip SNC3 | 200-350 | 320 | 35 | 80 | 60 | 110 | 0,73C – 0,95 | M |
| * | 3 | LC 50/200-350/170 flexCC Ip SNC3 | 200-350 | 250 | 50 | 85 | 60 | 110 | 0,69C – 0,95 | M |
| * | 4 | LC 65/200-350/210 flexCC Ip SNC3 | 200-350 | 250 | 65 | 85 | 60 | 110 | 0,76C – 0,95 | M |

¹ Values at output current of 350 mA

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.