

# Certificate of Compliance

**Certificate Number:**

UL-US-2338741-1

**Report Reference:**

E366084-20230918

**Issue Date:**

2024-07-19

Issued to:

**TRIDONIC GmbH & Co KG  
Faerbergasse 15 Dornbirn 6851  
Austria**

This certificate confirms that representative samples of:  
**OOQA2 - Light-emitting-diode Arrays - Component**  
**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**UL 8750, Edition 2, Issue Date 2015-09-15, Revision Date 2024-07-02**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch  
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-US-2338741-1  
**Report reference**     E366084-20230918  
**Date**                     2024-07-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
LLE FLEX 8mm 24V AAW BBBIm CCC EXC4 RDD, Where: LLE FLEX                     Designates product family – Linear Light Engine Flexible  8                                     (alphanumeric character) represents the width of the product  24 or 48                         (alphanumeric character) represents the voltage of the product  AA                                 (alphanumeric character) represents the rated power (W) of the product per meter can be one or two digits  BBBB                             (alphanumeric character) represents the light flux of the product per meter can be three or four digits  CCC                               (alphanumeric character combination) represents the colour rendering index + correlated colour temperature  SNC2, EXC2,                     alphanumeric character) SNC4 or EXC4 represents the layer and generation of the product  DD                                 (alphanumeric character combination) represents the total length of the product	LED Arrays, Modules, and Controllers



**David Picuch**  
 UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-US-2338741-1  
**Report reference**     E366084-20230918  
**Date**                     2024-07-19

LLE FLEX 8mm 24V AAW BBBBIm CCC SNC4 RDD, Where: LLE FLEX                     Designates product family – Linear Light Engine Flexible  8                                     (alphanumeric character) represents the width of the product  24 or 48                             (alphanumeric character) represents the voltage of the product  AA                                     (alphanumeric character) represents the rated power (W) of the product per meter can be one or two digits  BBBB                                     (alphanumeric character) represents the light flux of the product per meter can be three or four digits  CCC                                     (alphanumeric character combination) represents the colour rendering index + correlated colour    temperature  SNC2, EXC2,                     alphanumeric character) SNC4 or EXC4 represents the layer and generation of the product  DD                                     (alphanumeric character combination) represents the total length of the product	LED Arrays, Modules, and Controllers
LLE FLEX 8mm 48V AAW BBBBIm CCC EXC2 RDD, Where: LLE FLEX                     Designates product family – Linear Light Engine Flexible	LED Arrays, Modules, and Controllers



**David Picuch**  
 UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-US-2338741-1  
**Report reference**      E366084-20230918  
**Date**                      2024-07-19

<p>8                                      (alphanumeric character)                                                  represents the width of the                                                  product</p> <p>24 or 48                              (alphanumeric character)                                                  represents the voltage of the product</p> <p>AA                                      (alphanumeric character)                                                  represents the rated power (W) of                                                  the product per meter                                                  can be one or two digits</p> <p>BBBB                                      (alphanumeric character)                                                  represents the light flux of the product per                                                  meter                                                  can be three or four digits</p> <p>CCC                                      (alphanumeric character                                                  combination)                                                  represents the colour rendering index +                                                  correlated colour    temperature</p> <p>SNC2, EXC2,                              (alphanumeric character)                                                  SNC4 or EXC4 represents the layer and generation of the                                                  product</p> <p>DD                                      (alphanumeric character                                                  combination)                                                  represents the total length of the                                                  product</p>	
<p>LLE FLEX 8mm 48V AAW BBBBIm CCC SNC2 RDD,                                                  Where:                                                  LLE FLEX                              Designates product family –                                                  Linear Light Engine Flexible</p> <p>8                                      (alphanumeric character)                                                  represents the width of the                                                  product</p>	<p>LED Arrays, Modules, and Controllers</p>



**David Picuch**  
 UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

**Certificate number** UL-US-2338741-1  
**Report reference** E366084-20230918  
**Date** 2024-07-19

24 or 48	(alphanumeric character) represents the voltage of the product	
AA	(alphanumeric character) represents the rated power (W) of the product per meter can be one or two digits	
BBBB	(alphanumeric character) represents the light flux of the product per meter can be three or four digits	
CCC	(alphanumeric character combination) represents the colour rendering index + correlated colour temperature	
SNC2, EXC2, SNC4 or EXC4	(alphanumeric character) represents the layer and generation of the product	
DD	(alphanumeric character combination) represents the total length of the product	



David Picuch  
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# Certificate of Compliance

**Certificate Number:**

UL-CA-2333445-1

**Report Reference:**

E366084-20230918

**Issue Date:**

2024-07-19

Issued to:

**TRIDONIC GmbH & Co KG  
Faerbergasse 15 Dornbirn 6851  
Austria**

This certificate confirms that representative samples of:

**OOQA8 - Light-emitting-diode Arrays Certified for Canada - Component**

**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**CSA C22.2 No. 250.13, Edition 5, Issue Date 2022-05**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch  
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-CA-2333445-1  
**Report reference**     E366084-20230918  
**Date**                     2024-07-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
<p>LLE FLEX 8mm 24V AAW BBBBIm CCC EXC4 RDD, Where:</p> <p>LLE FLEX                     Designates product family –                                       Linear Light Engine Flexible</p> <p>8                                     (alphanumeric character)                                       represents the width of the                                       product</p> <p>24 or 48                         (alphanumeric character)                                       represents the voltage of the product</p> <p>AA                                 (alphanumeric character)                                       represents the rated power (W) of                                       the product per meter                                       can be one or two digits</p> <p>BBBB                             (alphanumeric character)                                       represents the light flux of the product per                                       meter                                       can be three or four digits</p> <p>CCC                                (alphanumeric character                                       combination)                                       represents the colour rendering index +                                       correlated colour    temperature</p> <p>SNC2, EXC2,                    alphanumeric character) SNC4 or EXC4 represents the layer and generation of the                                       product</p> <p>DD                                 (alphanumeric character                                       combination)                                       represents the total length of the                                       product</p>	<p>LED Arrays, Modules, and Controllers</p>



David Piecuch  
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-CA-2333445-1  
**Report reference**     E366084-20230918  
**Date**                     2024-07-19

LLE FLEX 8mm 24V AAW BBBBIm CCC SNC4 RDD, Where: LLE FLEX                     Designates product family – Linear Light Engine Flexible  8                                     (alphanumeric character) represents the width of the product  24 or 48                         (alphanumeric character) represents the voltage of the product  AA                                 (alphanumeric character) represents the rated power (W) of the product per meter can be one or two digits  BBBB                             (alphanumeric character) represents the light flux of the product per meter can be three or four digits  CCC                                (alphanumeric character combination) represents the colour rendering index + correlated colour    temperature  SNC2, EXC2,                     alphanumeric character) SNC4 or EXC4 represents the layer and generation of the product  DD                                 (alphanumeric character combination) represents the total length of the product	LED Arrays, Modules, and Controllers
LLE FLEX 8mm 48V AAW BBBBIm CCC EXC2 RDD, Where:	LED Arrays, Modules, and Controllers



David Piecuch  
 UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-CA-2333445-1  
**Report reference**     E366084-20230918  
**Date**                     2024-07-19

<p>LLE FLEX                     Designates product family – Linear Light Engine Flexible</p> <p style="margin-left: 40px;">8                                     (alphanumeric character)    represents the width of the    product</p> <p style="margin-left: 40px;">24 or 48                             (alphanumeric character)    represents the voltage of the product</p> <p style="margin-left: 40px;">AA                                     (alphanumeric character)    represents the rated power (W) of    the product per meter    can be one or two digits</p> <p style="margin-left: 40px;">BBBB                                 (alphanumeric character)    represents the light flux of the product per    meter    can be three or four digits</p> <p style="margin-left: 40px;">CCC                                     (alphanumeric character    combination)    represents the colour rendering index +    correlated colour    temperature</p> <p style="margin-left: 40px;">SNC2, EXC2,                     alphanumeric character) SNC4 or EXC4 represents the layer and generation of the    product</p> <p style="margin-left: 40px;">DD                                     (alphanumeric character    combination)    represents the total length of the    product</p>	
<p>LLE FLEX 8mm 48V AAW BBBBIm CCC SNC2 RDD, Where: LLE FLEX                     Designates product family – Linear Light Engine Flexible</p> <p style="margin-left: 40px;">8                                     (alphanumeric character)</p>	<p>LED Arrays, Modules, and Controllers</p>



David Piecuch  
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

**Certificate number** UL-CA-2333445-1  
**Report reference** E366084-20230918  
**Date** 2024-07-19

	represents the width of the product	
24 or 48	(alphanumeric character) represents the voltage of the product	
AA	(alphanumeric character) represents the rated power (W) of the product per meter can be one or two digits	
BBBB	(alphanumeric character) represents the light flux of the product per meter can be three or four digits	
CCC	(alphanumeric character combination) represents the colour rendering index + correlated colour temperature	
SNC2, EXC2, SNC4 or EXC4	(alphanumeric character) represents the layer and generation of the product	
DD	(alphanumeric character combination) represents the total length of the product	



David Piecuch  
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

