

OVE Austrian Electrotechnical Association
Eschenbachgasse 9 | 1010 Wien | Austria
ZVR: 327279890 | www.ove.at



OVE Certification
Kahlenberger Str. 2A | 1190 Wien | Austria
T +43 1 370 58 06 | certification@ove.at

ENEC Certification Body registered under ID # 11.

Validity of ENEC Licences can be checked at www.enec.com

LICENCE

to use the European Mark



Licence No.: **7590-324**

Date of issue: Wien, 2022 08 09
Rev. No.: 02 Wien, 2024 10 17

OVE the Austrian Electrotechnical Association as signatory to the **"Agreement on the use of a commonly agreed Mark of Conformity for certain electrical equipment complying with European Standards"** hereby grants the right to label the products mentioned hereunder and listed in the Annex with the Mark(s) shown above to the following company

Licensee: **Tridonic GmbH & Co KG**
Färbergasse 15
6851 Dornbirn
Austria

Product: **Electronic control gears for LED-modules**

Trade Mark: **TRIDONIC**

Series/Type: **LC ... flexC ... SNC3**

Basis for this given right is the conformity of the products with the requirements of the relevant Standard(s) as listed in the Annex and the fulfilment of articles 8 and 9 of the ENEC-Agreement by the manufacturer. This licence refers to the tested specimen and to all products manufactured strictly identical to the submitted one.

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

Österreichischer Verband für Elektrotechnik
Head of OVE Certification

Digitally signed by M. Neugebauer
on behalf of T. Neumayer
Email=m.neugebauer@ove.at
Dipl.-Ing. T. Neumayer



OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.



<i>Hersteller</i> <i>Manufacturer</i>	Tridonic GmbH & Co KG Färbergasse 15 6851 Dornbirn Austria
<i>Fertigungsstätte(n)</i> <i>Factory location(s)</i>	ID: 7590 ID: 87468 ID: 40926
<i>Typenbezeichnung</i> <i>Type reference</i>	LC ... flexC T-B SNC3, LC ... flexC T-G SNC3, LC ... flexC T-W SNC3, see page 4
* <i>Prüfbericht</i> <i>Test Report</i>	TR 87837-0001-01 ECS, TR 87837-0001-01a ECS, TR 87837-0001-02 ECS, TR 87837-0002-01 ECS, TR 87837-0002-01a ECS, TR 87837-0002-02 ECS, TR 7590-0125-02, TR 7590-0126-02
<i>Nationale Bestimmung(en)</i> <i>National Standard(s)</i>	OVE EN 61347-1:2021-09-01 OVE EN 61347-2-13:2017-11-01 OVE EN IEC 62384:2021-04-01
<i>Europannorm(en)</i> <i>European Standard(s)</i>	EN 61347-1:2015 + A1:2021 EN 61347-2-13:2014 + A1:2017 EN IEC 62384:2020
* <i>Ersatz für Zertifikat</i> <i>Superseded licence</i>	7590-324 Rev. 01 dated 2024 02 26 Items modified are marked with an asterisk (*)
<i>Anmerkung(en)</i> <i>Remark(s)</i>	--

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

<i>Nennspannung</i> <i>Rated voltage</i>	AC 220-240 V, 50/60 Hz
<i>Nennstrom (sec.)</i> <i>Rated current (sec.)</i>	see page 4
<i>Höchste Ausgangsspannung</i> <i>Max. output voltage</i>	see page 4
<i>Nennleistung</i> <i>Rated power</i>	see page 4
<i>Schutzklasse</i> <i>Class of protection</i>	CI.II
<i>Max. Betriebstemperatur t_c</i> <i>Rated max. operating temperature t_c</i>	see page 4
<i>Umgebungstemperatur t_a</i> <i>Rated ambient temperature t_a</i>	see page 4
<i>Maximale Gehäusetemperatur</i> <i>Rated maximum case temperature</i>	110°C
<i>Kurzschlußschutz</i> <i>Short-circuit protection</i>	Inherently short circuit proof controlgear.
<i>Klassifikation</i> <i>Classification</i>	Independent controlgear, constant current type, for use with luminaire track system.

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

TRADEMARK / TYPECODE		Classification I...Independent	Rated output current	Maximum output voltage (no-load)	Rated output power	Rated max. operating temperature (tc) ¹	Maximum ambient temperature (ta)	Maximum case temperature	Circuit power factor	Case
TRIDONIC										Metal (M) Plastic (P)
			[mA]	[V]	[W]	[°C]	[°C]	[°C]	λ	
1	LC 15/200-350/42 flexC T-B SNC3	I	200-350	60 SELV	15	50/55/60	35	110	0,7C-0,95	P
2	LC 15/200-350/42 flexC T-G SNC3	I	200-350	60 SELV	15	50/55/60	35	110	0,7C-0,95	P
3	LC 15/200-350/42 flexC T-W SNC3	I	200-350	60 SELV	15	50/55/60	35	110	0,7C-0,95	P
4	LC 25/450-600/42 flexC T-B SNC3	I	450-600	60 SELV	25	60/65/70	35	110	0,83C-0,96	P
5	LC 25/450-600/42 flexC T-G SNC3	I	450-600	60 SELV	25	60/65/70	35	110	0,83C-0,96	P
6	LC 25/450-600/42 flexC T-W SNC3	I	450-600	60 SELV	25	60/65/70	35	110	0,83C-0,96	P
7	LC 34/650-800/42 flexC T-B SNC3	I	650-800	60 SELV	34	60/65	35	110	0,8C-0,96	P
8	LC 34/650-800/42 flexC T-G SNC3	I	650-800	60 SELV	34	60/65	35	110	0,8C-0,96	P
9	LC 34/650-800/42 flexC T-W SNC3	I	650-800	60 SELV	34	60/65	35	110	0,8C-0,96	P
10	LC 42/900-1050/40 flexC T-B SNC3	I	900-1050	60 SELV	42	75/80	35	110	0,87C-0,97	P
11	LC 42/900-1050/40 flexC T-G SNC3	I	900-1050	60 SELV	42	75/80	35	110	0,87C-0,97	P
12	LC 42/900-1050/40 flexC T-W SNC3	I	900-1050	60 SELV	42	75/80	35	110	0,87C-0,97	P

¹ Depending on selected output current, see respective datasheet.

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.