



# 中国国家强制性产品认证证书

证书编号：2025011002792645

## 认证委托人名称及地址

锐高照明电子（上海）有限公司  
中国（上海）自由贸易试验区富特北路 215 号第二层 F12 部位

## 生产者名称及地址

锐高照明电子（上海）有限公司  
中国（上海）自由贸易试验区富特北路 215 号第二层 F12 部位

## 生产企业名称及地址

锐高照明电子（深圳）有限公司  
深圳市龙华区观澜街道库坑社区龙华大道 7301 号 A3 栋一层二层

## 产品名称和系列、型号、规格

LED 模块交直流电子控制装置（LED 控制装置，控制端口调光，内装式，自耦式，EL，恒流模式，tc: 85°C，定温热保护：110°C）  
见附页。220-240V~50/60Hz, 220-240VDC

## 产品标准和技术要求

GB 17625.1-2022; GB/T 17743-2021; GB/T 19510.1-2023; GB/T 19510.213-2023  
上述产品符合《强制性产品认证实施规则 照明电器》（CNCA-C10-01:2014）的要求，特发此证。

发证日期：2025 年 07 月 08 日 有效期至：2030 年 07 月 07 日

证书信息和有效性可扫描下方二维码或登录发证机构网站查验，  
也可在认监委网站（[www.cnca.gov.cn](http://www.cnca.gov.cn)）查询。



签发：

谢肇煦



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司





# 中国国家强制性产品认证证书

证书编号: 2025011002792645


证书附页: 第 1 页 共 1 页

序号	产品型号	参数
1.	LC 100/300-1050/230 DA Ip SNC4	输出: 300-1050mA(恒流可调), Uout=250Vdc, 配套光源: 17.3-100W LED 模块

拨码开关:

Irated(mA)	Pin1	Pin2	Pin3	Pin4	ta	Irated(mA)	Pin1	Pin2	Pin3	Pin4	ta
300	-	-	-	-	-20...+70°C	700	ON	-	-	-	-20...+60°C
350	-	-	-	ON		750	ON	-	-	ON	
400	-	-	ON	-	800	ON	-	ON	-		
450	-	-	ON	ON	850	ON	-	ON	ON		
500	-	ON	-	-	900	ON	ON	-	-		
550	-	ON	-	ON	950	ON	ON	-	ON		
600	-	ON	ON	-	1000	ON	ON	ON	-		
650	-	ON	ON	ON	1050	ON	ON	ON	ON		

"-" = OFF

输入: 220-240V $\sim$  0/50/60Hz, 恒流,  $t_c:85^\circ\text{C}$ , 内装式, 自耦式, 



本页为证书附页, 应与证书主页同时使用。



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，  
不得单独使用  
This translated document  
does not have legal validity and  
cannot be used in isolation

**CERTIFICATE NO.:** 2025011002792645

## NAME AND ADDRESS OF THE APPLICANT

Tridonic (Shanghai) Co., Ltd.  
F12, 2nd Floor, No.215, North Fute Road, China (Shanghai) Pilot Free Trade Zone, Shanghai City,  
P.R.China

## NAME AND ADDRESS OF THE MANUFACTURER

Tridonic (Shanghai) Co., Ltd.  
F12, 2nd Floor, No.215, North Fute Road, China (Shanghai) Pilot Free Trade Zone, Shanghai City,  
P.R.China

## NAME AND LOCATION OF THE FACTORY

TridonicAtco (Shenzhen) Co., Ltd.  
1-2F,Building A3, 7301 Longhua Avenue, Kukeng Community, Guanlan Street, Longhua District,  
Shenzhen

## PRODUCT NAME,MODEL AND SPECIFICATION

A.C. or D.C. Supplied Electronic Controlgear for LED Modules (LED Controlgear, Controlled Port  
Dimming, Built-in, Auto-wound Controlgear, EL, Constant Current Mode, tc:85°C, Temperature  
Declared Thermally Protected: 110°C)  
See Appendix. 220-240V ~ 50/60Hz, 220-240VDC

## STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022;GB/T 17743-2021;GB/T 19510.1-2023;GB/T 19510.213-2023

This is to certify that the above mentioned product(s) complies with the requirements of  
implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014).

**Valid from:** Jul.08,2025

**Valid until:** Jul.07,2030

The certificate information and validity could be checked by scanning the QR code below or logging in to  
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).



SIGNATURE:

谢肇煦



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.







# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，  
不得单独使用  
This translated document  
does not have legal validity and  
cannot be used in isolation

CERTIFICATE NO. : 2025011002792645

Appendix: Page 1 of 1

序号	产品型号	参数																																																																																														
1.	LC 100/300-1050/230 DA lp SNC4	输出: 300-1050mA(恒流可调), U <sub>out</sub> =250Vdc, 配套光源: 17.3-100W LED 模块																																																																																														
拨码开关:																																																																																																
<table border="1"> <thead> <tr> <th>I<sub>rated</sub>(mA)</th> <th>Pin1</th> <th>Pin2</th> <th>Pin3</th> <th>Pin4</th> <th>ta</th> <th>I<sub>rated</sub>(mA)</th> <th>Pin1</th> <th>Pin2</th> <th>Pin3</th> <th>Pin4</th> <th>ta</th> </tr> </thead> <tbody> <tr> <td>300</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td rowspan="2">-20...+70°C</td> <td>700</td> <td>ON</td> <td>-</td> <td>-</td> <td>-</td> <td rowspan="10">-20...+60°C</td> </tr> <tr> <td>350</td> <td>-</td> <td>-</td> <td>-</td> <td>ON</td> <td>750</td> <td>ON</td> <td>-</td> <td>-</td> <td>ON</td> </tr> <tr> <td>400</td> <td>-</td> <td>-</td> <td>ON</td> <td>-</td> <td>800</td> <td>ON</td> <td>-</td> <td>ON</td> <td>-</td> </tr> <tr> <td>450</td> <td>-</td> <td>-</td> <td>ON</td> <td>ON</td> <td>850</td> <td>ON</td> <td>-</td> <td>ON</td> <td>ON</td> </tr> <tr> <td>500</td> <td>-</td> <td>ON</td> <td>-</td> <td>-</td> <td>900</td> <td>ON</td> <td>ON</td> <td>-</td> <td>-</td> </tr> <tr> <td>550</td> <td>-</td> <td>ON</td> <td>-</td> <td>ON</td> <td>950</td> <td>ON</td> <td>ON</td> <td>-</td> <td>ON</td> </tr> <tr> <td>600</td> <td>-</td> <td>ON</td> <td>ON</td> <td>-</td> <td>1000</td> <td>ON</td> <td>ON</td> <td>ON</td> <td>-</td> </tr> <tr> <td>650</td> <td>-</td> <td>ON</td> <td>ON</td> <td>ON</td> <td>1050</td> <td>ON</td> <td>ON</td> <td>ON</td> <td>ON</td> </tr> </tbody> </table>			I <sub>rated</sub> (mA)	Pin1	Pin2	Pin3	Pin4	ta	I <sub>rated</sub> (mA)	Pin1	Pin2	Pin3	Pin4	ta	300	-	-	-	-	-20...+70°C	700	ON	-	-	-	-20...+60°C	350	-	-	-	ON	750	ON	-	-	ON	400	-	-	ON	-	800	ON	-	ON	-	450	-	-	ON	ON	850	ON	-	ON	ON	500	-	ON	-	-	900	ON	ON	-	-	550	-	ON	-	ON	950	ON	ON	-	ON	600	-	ON	ON	-	1000	ON	ON	ON	-	650	-	ON	ON	ON	1050	ON	ON	ON	ON
I <sub>rated</sub> (mA)	Pin1	Pin2	Pin3	Pin4	ta	I <sub>rated</sub> (mA)	Pin1	Pin2	Pin3	Pin4	ta																																																																																					
300	-	-	-	-	-20...+70°C	700	ON	-	-	-	-20...+60°C																																																																																					
350	-	-	-	ON		750	ON	-	-	ON																																																																																						
400	-	-	ON	-	800	ON	-	ON	-																																																																																							
450	-	-	ON	ON	850	ON	-	ON	ON																																																																																							
500	-	ON	-	-	900	ON	ON	-	-																																																																																							
550	-	ON	-	ON	950	ON	ON	-	ON																																																																																							
600	-	ON	ON	-	1000	ON	ON	ON	-																																																																																							
650	-	ON	ON	ON	1050	ON	ON	ON	ON																																																																																							
“-” = OFF																																																																																																
输入: 220-240V $\sim$ 0/50/60Hz, 恒流, t <sub>c</sub> :85°C, 内装式, 自耦式,  , 																																																																																																

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.