



Product Service

CERTIFICATE

No. U6 079054 0053 Rev. 04

Holder of Certificate: Tridonic GmbH & Co KG
Färbergasse 15
6851 Dornbirn
AUSTRIA

Certification Mark:



Product: Electronic controlgear for LED modules
(LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215020605

Date, 2025-12-05

(Taylor Yao)

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

CERTIFICATE

No. U6 079054 0053 Rev. 04

Model(s): LC 19/200-350/54 flexC Ip SNC4;
 LC 38/400-700/54 flexC Ip SNC4;
 LC 57/700-1050/54 flexC Ip SNC4;
 LC 75/1100-1400/54 flexC Ip SNC4

Brand Name: TRIDONIC



Parameters:

Rated Input Voltage: 220-240VAC/DC
 Rated Frequency: 50/60Hz (for 220-240VAC)
 Rated Input Current: See below table for details
 Rated Output: See below table for details
 Protection against Electric Shock: SELV
 Method of Installation: Built-in
 Type of Output: Constant current type
 tc: See below table for details

Model	Rated Input Current (A)	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W)	Value of tc (°C)
LC 19/200-350/54 flexC Ip SNC4	0.100	20-54	200	60	10.8	75
			225		12.15	75
			250		13.5	75
			275		14.85	80
			300		16.2	80
			325		17.55	80
			350		18.9	80
LC 38/400-700/54 flexC Ip SNC4	0.191	20-54	400	60	21.6	80
			450		24.3	80
			500		27.0	85
			550		29.7	85
			600		32.4	85
			650		35.1	85
			700		37.8	90
LC 57/700-1050/54 flexC Ip SNC4	0.282	20-54	700	60	37.8	85
			750		40.5	85
			800		43.2	90
			850		45.9	90
			900		48.6	90
			950		51.3	90
			1000		54.0	90
			1050		56.7	90



CERTIFICATE

No. U6 079054 0053 Rev. 04

LC 75/1100-1400/54 flexC Ip SNC4	0.370	20-54	1100	60	59.4	85
			1150		62.1	85
			1200		64.8	85
			1250		67.5	90
			1300		70.2	90
			1350		72.9	90
			1400		75.6	90

Tested according to:

EN 61347-1:2015/A1:2021
 EN 61347-2-13:2014/A1:2017
 EN IEC 62384:2020

Production Facility(ies):

114313