

OVE Austrian Electrotechnical Association
Eschenbachgasse 9 | 1010 Wien | Austria
ZVR: 327279890 | www.ove.at



OVE Certification
Kahlenberger Str. 2A | 1190 Wien | Austria
T +43 1 370 58 06 | certification@ove.at

ENEC Certification Body registered under ID # 11.

Validity of ENEC Licences can be checked at www.enec.com

LICENCE

to use the European Mark



Licence No.: **7590-363**

Date of issue: Wien, 2025 09 02
Rev. No.: 02 Wien, 2026 05 12

OVE the Austrian Electrotechnical Association as signatory to the **"Agreement on the use of a commonly agreed Mark of Conformity for certain electrical equipment complying with European Standards"** hereby grants the right to label the products mentioned hereunder and listed in the Annex with the Mark(s) shown above to the following company

Licensee: **Tridonic GmbH & Co KG**
Färbergasse 15
6851 Dornbirn
Austria

Product: **Electronic control gears for LED-modules**

Trade Mark: **TRIDONIC**

Series/Type: **LC ... DA Ip SNC4**

Basis for this given right is the conformity of the products with the requirements of the relevant Standard(s) as listed in the Annex and the fulfilment of articles 8 and 9 of the ENEC-Agreement by the manufacturer. This licence refers to the tested specimen and to all products manufactured strictly identical to the submitted one.

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

Österreichischer Verband für Elektrotechnik
Head of OVE Certification

T. Neumayer

Digitally signed by T. Neumayer
Email=t.neumayer@ove.at

Dipl.-Ing. T. Neumayer



OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.



<i>Hersteller Manufacturer</i>	Tridonic GmbH & Co KG Färbergasse 15 6851 Dornbirn Austria
<i>Fertigungsstätte(n) Factory location(s)</i>	ID: 7590 ID: 87468 ID: 40926
<i>* Typenbezeichnung Type reference</i>	LC ... DA Ip SNC4 see page 4
<i>* Prüfbericht Test Report</i>	TR 87837-0190-01 ECS, TR 87837-0190-02 ECS, TR 87837-0191-01 ECS, TR 87837-0191-02 ECS, TR 87837-0192-01 ECS, TR 87837-0192-02 ECS, TR 87837-0193-01 ECS, TR 87837-0193-02 ECS
<i>Nationale Bestimmung(en) National Standard(s)</i>	OVE EN 61347-1:2021-09-01 OVE EN 61347-2-13:2017-11-01 OVE EN IEC 62384:2021-04-01
<i>Europannorm(en) European Standard(s)</i>	EN 61347-1:2015 + A1:2021 EN 61347-2-13:2014 + A1:2017 EN IEC 62384:2020
<i>* Ersatz für Zertifikat Superseded licence</i>	7590-363 Rev. 01 dated 2025 11 03 Items modified are marked with an asterisk (*)
<i>Anmerkung(en) Remark(s)</i>	Complies with the additional requirements for emergency lighting according Annex J of EN 61347-2-13:2014 + A1:2017.

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

<i>Bemessungsversorgungsspannung</i> <i>Rated supply voltage</i>	AC 220-240 V, 50/60 Hz; DC 220-240 V
<i>Bemessungsausgangsstrom (I_{rated})</i> <i>Rated output current (I_{rated})</i>	see page 4
<i>Höchste Arbeitsspannung (U-OUT)</i> <i>Maximum working voltage (U-OUT)</i>	see page 4
<i>Nennleistung</i> <i>Rated power</i>	see page 4
<i>Max. Betriebstemperatur t_c</i> <i>Rated max. operating temperature t_c</i>	see page 4
<i>Umgebungstemperatur t_a</i> <i>Rated ambient temperature t_a</i>	see page 4
<i>Maximale Gehäusetemperatur</i> <i>Maximum case temperature</i>	110°C
<i>Kurzschlußschutz</i> <i>Short-circuit protection</i>	Inherently short circuit proof control gear.
<i>Klassifikation</i> <i>Classification</i>	Built-in electronic controlgears providing SELV, constant current type.

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

TRADEMARK / TYPECODE		Classification B...Built-in I...Independent	Rated output current	Maximum output voltage (no-load)	Rated output power	Rated max. operating temperature (tc) ¹	Maximum ambient temperature (ta) ¹	Maximum case temperature	Circuit power factor (230V, 50Hz, full load)	Case
TRIDONIC										Metal (M) Plastic (P)
			[mA]	[V]	[W]	[°C]	[°C]	[°C]	λ	
1	LC 20/100-450/54 DA Ip SNC4	B	100-450	60 (SELV)	2-20	75	65	110	0,43C - 0,96	M
2	LC 35/250-700/54 DA Ip SNC4	B	250-700	60 (SELV)	5-35	75	65	110	0,5C - 0,96	M
3	LC 55/500-1050/54 DA Ip SNC4	B	500-1050	60 (SELV)	10-55	85	70	110	0,67C - 0,98	M
4	LC 75/900-1900/54 DA Ip SNC4	B	900-1900	60 (SELV)	18-75	87	70	110	0,74C - 0,98	M

¹ Depending on selected output current, see label or datasheet

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.